

1. Product Name

PAC-RCB RESILIENT CHANNEL BACKER

- **MODEL NUMBER:** PAC-RCB Sound Isolator.
 - PAC-RCB Sound Isolator

2. Manufacturer

PAC International, LLC
7260 W Azure Dr
Suite 140-213
Las Vegas, NV 89130
Phone: (866) 774-2100
Fax: (866) 649-2710
Email: info@pac-intl.com
Web: www.pac-intl.com

3. Product Description

PACPRO SERIES, RESILIENT CHANNEL BACKER MODEL NUMBER: PAC-RCB

PAC-RCB is designed for use with all resilient channel wall systems where support for heavy loads like cabinets, bookshelves, headboards, shelving, etc. is required. The PAC-RCB stops the noise and vibration that typically would be allowed to transfer from room to room through the structure when heavy loads are mounted directly to the wall framing when resilient channels are used.

Materials and Composition

The PAC-RCB isolator is made of natural rubber and/or manufactured rubber compound, a product specific fastener, and steel parts. All isolation components are provided by the manufacturer. The Supporting cross member/backer (wood or steel) is supplied by others.


Environmental Considerations

The PAC-RCB may contribute to LEED points by reducing materials needed to achieve high STC ratings. The rubber and Steel portions can be recycled.

Weight-bearing Information

The PAC-RCB has an Acoustical Design Load (ADL) rating of up to 25 pounds per bracket (two rubber isolators) or fifty (50#) pounds per stud bay per cross member/backer. The PAC-RCB fastens directly to the wall framing and supports a steel or wood backer section/cross member for mounting cabinets, headboards, handrails, shelving, heavy art, etc.

PAC-RCB



Product Limitations

For interior use only with operating temperatures of 40–100 degrees F (4.4–37.8 degrees C).

4. Technical Data

Division:	05-7000
	09-2000
	09-2240
	09-8000
	09-8500
	10-2000
	12 3800

Applicable Standards

ASTM International (ASTM)

- **ASTM E90** Standard Test Method for Laboratory Measurement of Airborne Sound Transmission Loss of Building Partitions and Elements
- **ASTM E336** Standard Test Method for Measurement of Airborne Sound Attenuation between Rooms in Buildings
- **ASTM E413** Classification for Rating Sound Insulation

5. Installation

General installation:

Follow manufacturer's specific installation instructions.

- Install PAC-RCB Resilient Channel Backer following the manufacturer recommendations.
- Trim bridge/backer/cross blocking (by others) material to fit between wall studs minus 1 inch.
 - For wood framed walls use min. 2x4 or 2x6 nominal wood section.
 - For steel framed walls use min. 20 Ga 3-1/2" steel stud and track section.
- Install the PAC-RCB Isolators to the wood or steel backers using screws provided by the manufacturer
Do not allow the backer/bridge (block) to contact the metal part of the PAC-RCB.
- Use the PAC RC-Boost install tool to help set fastener depth when installing the RC-Boost isolator to the backer/cross member.
- Adjust the depth setting of the screw gun so the head of the PAC-RCB mounting screw only touches the rubber isolator. Do not compress the rubber.
- Install the PAC-RCB on the wall framing to support the top and bottom of upper cabinets, and the top of the lower cabinets.
- Install the PAC-RCB in between studs to support other items, listed above.
- Fasten the PAC-RCB to the structure
 - For wood framed walls, use 1-5/8" long, wafer head coarse thread screws, two per bracket.
 - For steel framed walls, use a min length #8 x 1/2" long self-drilling fine thread screw
- Max acoustical design load of each PAC-RCB section is 25 Lbs per PAC RCB.
- Max stud spacing for use of the PAC-RCB is 24" on center.
- Flanking Noise:
 - Review installation details to prevent structure-borne flanking noise
 - Do not allow metal part of PAC-RCB to contact wall framing members.

- Gypsum Board:
 - Install PAC Perimeter tape to side walls and ceiling where gypsum board abuts other walls and ceilings.
 - Install gypsum board on wall perpendicular to the Resilient Channel. Perimeter of gypsum board should be in contact with the PAC perimeter tape. Caulk over gap with acoustical sealant.
 - Install gypsum board in accordance with ASTM C840 as specified in Section 09250
- Cabinets:
 - Install cabinets with wood or steel screws long enough to penetrate the gypsum board and the wood PAC-RCB 1-1/2 inch, and steel 1 inch.
 - Install upper cabinets to Top of cabinet and bottom of cabinet PAC-RCB Backing / Cross member only.
Do not screw into the studs.
 - Install base cabinets to the top of base cabinet PAC-RCB blocking/cross member only.
Do not screw into the studs.
- Acoustical Sealant:
 - Seal potential air leaks with acoustical sealant to achieve best Field Sound Transmission Class (FSTC)
 - Seal electrical outlets and penetrations with acoustical sealant
 - Apply fire-rated acoustical sealant at locations where fire-rated assembly is required
- Putty Pad Sealant: acoustically seal with putty pads, electrical boxes in walls and ceilings in which resilient sound isolation clips are used

6. Availability and Cost

Please contact PAC International, LLC. for availability and pricing information.

7. Warranty

PAC-RCB clips are guaranteed free of manufacturer defects. Only remedy is the replacement of the defective component or components. Manufacturer is not liable for delays or extra costs.



World Leader
in Noise
Control
Solutions



GYPSUM BOARD ASSEMBLIES 2021

PAC INTERNATIONAL, LLC.

8. Maintenance

No maintenance is necessary.

9. Technical Services

PAC International LLC. offers online product pages, installation guides, and specification sheets.

Technical information can be found on the website, www.pac-intl.com www.pacinternationalllc.com or by calling 866-774-2100

Fire ratings, sound test assemblies, CAD drawings, assembly drawings and clip specifications are also on the website.

10. Filing Systems

- Additional product information is available from the manufacturer upon request