

1. Product Name

- RSIC-1.5 CRC Boost Resilient Sound Clip..
 - RSIC-1.5 CRC Resilient Sound Clip

2. Manufacturer

PAC International, LLC
7260 W Azure Dr
Suite 140-213
Las Vegas, NV 89130
Phone: (866) 774-2100
Fax: (866) 649-2710
Email: info@pac-intl.com
Web: www.pac-intl.com

3. Product Description

RSIC-1.5 CRC

The RSIC-1.5 CRC is designed for use with ceiling system where noise control is needed. The RSIC-1.5 CRC assembly decouples and isolates the gypsum board or other sheet goods from the structure increasing the acoustical performance of the system.

The RSIC-1.5 CRC stops the noise and vibrations that typically would be allowed to transfer through the structure.

Materials and Composition

The RSIC-1.5 CRC rubber isolators are made of rubber and/or manufactured rubber compound, and steel parts.

Environmental Considerations

The RSIC-1.5 CRC may contribute to LEEDS points, by reducing materials needed to typically reach the high noise control levels the RSIC-1.5crc reaches.

The rubber RSIC-1.5 CRC fittings can be recycled.

The steel recycled content is less than 10 percent as required for fire life and safety regulations.

Weight-bearing Information

With an acoustical design load rating of 36 pounds per isolator, The RSIC-1.5 CRC clip can support up to two layers of 5/8 inch gypsum board when spaced at 24 x 48 inches on center. 16" x 48" oc for three layers of Gypsum board. For heavier systems increase the number of isolators and channel to support the additional weight of the system. The RSIC-1.5 CRC clip clips to 1.5" CRC channel. Ceiling height is determined by the position of the 1.5" CRC channel in the ceiling.



RSIC-1.5 CRC

Product Limitations

For interior use only with operating temperatures of 40–100 degrees F (4.4–37.8 degrees C). Max load 36 Lbs

4. Technical Data

Divisions:	09-2000
	09-8000
	09-8500
	10-2000

Applicable Standards

ASTM International (ASTM)

- **ASTM E90** Standard Test Method for Laboratory Measurement of Airborne Sound Transmission Loss of Building Partitions and Elements

- **ASTM E413** Classification for Rating Sound Insulation Underwriters Laboratories (UL)

- **UL Fire Resistance Directory**; www.ul.com or visit [here](#).

5. Installation

General installation:

follow manufacturer's specific installation instructions.

- Install resilient sound isolation clips Resilient channel following the manufacturer recommendations.
- Clip the resilient sound isolation clips to the 1.5" CRC channel, then screw the RSIC-1.5 CRC to the 1.5" CRC channel.
- Space resilient sound isolation clips at maximum of 24 x 48 inches (600 x 460 mm) on center ceilings
- Do not exceed design load (pull and shear) of 36 pounds per isolation clip



World Leader
in Noise
Control
Solutions



GYPSUM BOARD ASSEMBLIES 09-21-16

PAC INTERNATIONAL, LLC.

- Install 7/8" 25 Ga drywall furring channel (Hat Channel) into RSIC1.5 CRC at a maximum of 24 x 48 inches (600 x 460 mm) on center.
- Splicing Drywall Furring Channels:
 - Splice drywall furring channels with minimum of six inch (150 mm) laps
 - Secure laps with two framing screws or 18 gauge tie wire double wrapped
 - Locate splices between resilient sound isolation clips
 - Do not locate splices on resilient sound isolation clips
- Flanking Noise:
 - Review installation details to prevent structure-borne flanking noise
 - Do not allow drywall furring channels or gypsum board to contact wall framing members
- Gypsum Board:
 - Install gypsum board in perpendicular to the Drywall Furring Channel. Leave a 1/4 inch (6 mm) gap around perimeter for acoustical sealant application
 - Install gypsum board in accordance with ASTM C840 as specified in Section 09250
- Acoustical Sealant:
 - Seal potential air leaks with acoustical sealant to achieve best Field Sound Transmission Class (FSTC)
 - Seal electrical outlets and penetrations with acoustical sealant
 - Apply fire-rated acoustical sealant at locations where fire-rated assembly is required
- Putty Pad Sealant: acoustically seal with putty pads, electrical boxes in walls and ceilings in which resilient sound isolation clips are used

6. Availability and Cost

Please contact PAC International, LLC. for availability and pricing information.

7. Warranty

RSIC-1.5 CRC clips has no warranty.

8. Maintenance

No maintenance is necessary.

9. Technical Services

PAC International Inc. offers online product pages, installation guides, and specification sheets. Technical information can be found on the website, www.pac-intl.com or by calling 866-774-2100, ext. 101 or 801. Fire ratings, sound test assemblies, CAD drawings, assembly drawings and clip specifications are also on the website.

10. Filing Systems

- Additional product information is available from the manufacturer upon request