© PAC International, LLC. All Rights Reserved. • (866) 774-2100 • Fax (866) 649-2710 RSIC® is a registered Trade Mark of PAC International, LLC.

RSIC-SI-CRC2 LP

The RSIC-SI-CRC2 LP is designed to isolate the ceiling at greater spans with two 1.5" x 16 Ga cold-rolled channel and furring channel (25 or 20 Ga). The RSIC-SI-CRC2 LP clip is available in 10 lb, 20 lb, 30 lb, 40 lb, 60 lb, 80 lb, 100 lb, 120 lb versions. Maximum spacing for the RSIC-SI-CRC2 LP is 48" x 72" oc.

	Condo
Concrete	Commercial
Apartment	Recording Studio
Retail	Home Theater
Conference Rooms	Commercial theater

RSIC-SI-CRC2	ΙP	specifications.
		specifications.

Acoustical design load:	10 lbs to 120 lbs	
Total deflection	1 inch	
Double deflection	YES (+/- ½")	
Pre-Calibrated	YES	
Pre-Assembled	YES	
Adjustable	YES	
Cavity min	1 inch (wood)	
Cavity Max	9 inches	
Adjustment limit	6 inches	
Use on Ceilings	YES	
Use on walls	NO	
New Construction	YES	
Tested, Engineered, Designed, and Calibrated In USA		







